

Container 'wordpress-technikkultur'

Ressourcen

- 1 GB RAM
- 2 Cores
- 5 GB HDD (root-fs)
- 35 GB HDD (data)

System

- interne IPs
 - 10.2.0.14, fd00:10:2:0::14
 - 10.3.0.14, fd00:10:3:0::14

Dienste

- Nextcloud (via NGINX)

Installation

- Standard-Template mit Benutzern

NGINX / PHP

1. NGINX und PHP-FPM installieren
 - **sudo apt-get install php7.3 php7.3-cli php7.3-fpm php7.3-curl php7.3-gd php7.3-json php7.3-xml php7.3-mbstring php7.3-zip php7.3-mysql php7.3-bz2 php7.3-intl php7.3-bcmath php7.3-gmp php-imagick nginx**
2. Default-Konfiguration anpassen

/etc/nginx/sites-available/default

```
server {
    listen 80 default_server;
    listen [::]:80 default_server;

    root /var/www/public_html;

    # Add index.php to the list if you are using PHP
    index index.php index.html /index.php$request_uri;

    server_name _;

    # set max upload size
    client_max_body_size 512M;
    fastcgi_buffers 64 4K;

    # Enable gzip but do not remove ETag headers
    gzip on;
    gzip_vary on;
    gzip_comp_level 4;
    gzip_min_length 256;
    gzip_proxied expired no-cache no-store private no_last_modified no_etag auth;
    gzip_types application/atom+xml application/javascript application/json
application/ld+json application/manifest+json application/rss+xml
application/vnd.geo+json application/vnd.ms-fontobject application/x-font-ttf
application/x-web-app-manifest+json application/xhtml+xml application/xml font/opentype
image/bmp image/svg+xml image/x-icon text/cache-manifest text/css text/plain text/vcard
```

```

text/vnd.rim.location.xloc text/vtt text/x-component text/x-cross-domain-policy;

# HTTP response headers borrowed from Nextcloud `.htaccess`
add_header Referrer-Policy "no-referrer" always;
add_header X-Content-Type-Options "nosniff" always;
add_header X-Download-Options "noopen" always;
add_header X-Frame-Options "SAMEORIGIN" always;
add_header X-Permitted-Cross-Domain-Policies "none" always;
add_header X-Robots-Tag "none" always;
add_header X-XSS-Protection "1; mode=block" always;

# Remove X-Powered-By, which is an information leak
fastcgi_hide_header X-Powered-By;

# Rule borrowed from `.htaccess` to handle Microsoft DAV clients
location = / {
    if ( $http_user_agent ~ ^DavClnt ) {
        return 302 /remote.php/webdav/$is_args$args;
    }
}

location = /robots.txt {
    allow all;
    log_not_found off;
    access_log off;
}

# Make a regex exception for `/.well-known` so that clients can still
# access it despite the existence of the regex rule
# `location ~ /\.(|autotest|...)` which would otherwise handle requests
# for `/.well-known`.
location ^~ /.well-known {
    # The following 6 rules are borrowed from `.htaccess`
    last;
    rewrite ^/\..well-known/host-meta\.json /public.php?service=host-meta-json
last;
    rewrite ^/\..well-known/host-meta /public.php?service=host-meta
last;
    rewrite ^/\..well-known/webfinger /public.php?service=webfinger
last;
    rewrite ^/\..well-known/nodeinfo /public.php?service=nodeinfo
last;
    location = /.well-known/carddav { return 301 /remote.php/dav/; }
    location = /.well-known/caldav { return 301 /remote.php/dav/; }
    try_files $uri $uri/ =404;
}

# Rules borrowed from `.htaccess` to hide certain paths from clients
return 404; }
location ~ ^/(?:(?:build|tests|config|lib|3rdparty|templates|data)?(?:$|/)) {
return 404; }
location ~ ^/(?!(?:\..|autotest|occ|issue|indie|db_|console)) { return
404; }

# Ensure this block, which passes PHP files to the PHP process, is above the
blocks
# which handle static assets (as seen below). If this block is not declared
first,
# then Nginx will encounter an infinite rewriting loop when it prepends
`/index.php`
# to the URI, resulting in a HTTP 500 error response.
location ~ \.php(?:$|/) {
    fastcgi_split_path_info ^(.+?\.php)(/.*)$;

```

```

    set $path_info $fastcgi_path_info;

    try_files $fastcgi_script_name =404;

    include fastcgi_params;
    fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;
    fastcgi_param PATH_INFO $path_info;
    fastcgi_param HTTPS on;

    fastcgi_param modHeadersAvailable true;      # Avoid sending the
security headers twice
    fastcgi_param front_controller_active true;  # Enable pretty urls
    #fastcgi_pass php-handler;
    fastcgi_pass unix:/run/php/php7.3-fpm.sock;

    fastcgi_intercept_errors on;
    fastcgi_request_buffering off;
}

location ~ \.(?:css|js|svg|gif)$ {
    try_files $uri /index.php$request_uri;
    expires 6M;          # Cache-Control policy borrowed from `.htaccess`
    access_log off;      # Optional: Don't log access to assets
}

location ~ \.woff2?$ {
    try_files $uri /index.php$request_uri;
    expires 7d;          # Cache-Control policy borrowed from `.htaccess`
    access_log off;      # Optional: Don't log access to assets
}

location / {
    try_files $uri $uri/ /index.php$request_uri;
}
}

```

3. PHP-Konfiguration für Upload anpassen

/etc/php/7.3/fpm/pool.d/www.conf

```

...
clear_env = no
...
env[HOSTNAME] = $HOSTNAME
env[PATH] = /usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin
env[TMP] = /tmp
env[TMPDIR] = /tmp
env[TEMP] = /tmp
...

```

4. PHP-Konfiguration für Upload anpassen

/etc/php/7.3/fpm/php.ini

```

...
; Output buffering is a mechanism for controlling how much output data
; (excluding headers and cookies) PHP should keep internally before pushing that
; data to the client. If your application's output exceeds this setting, PHP
; will send that data in chunks of roughly the size you specify.
; Turning on this setting and managing its maximum buffer size can yield some
; interesting side-effects depending on your application and web server.

```

```

; You may be able to send headers and cookies after you've already sent output
; through print or echo. You also may see performance benefits if your server is
; emitting less packets due to buffered output versus PHP streaming the output
; as it gets it. On production servers, 4096 bytes is a good setting for performance
; reasons.
output_buffering = 0
...
; Maximum execution time of each script, in seconds
; http://php.net/max-execution-time
; Note: This directive is hardcoded to 0 for the CLI SAPI
max_execution_time = 1800
...
; Maximum amount of time each script may spend parsing request data. It's a good
; idea to limit this time on productions servers in order to eliminate unexpectedly
; long running scripts.
max_input_time = 1800
...
; Maximum amount of memory a script may consume (128MB)
; http://php.net/memory-limit
memory_limit = 512M
...
; Temporary directory for HTTP uploaded files (will use system default if not
; specified).
; http://php.net/upload-tmp-dir
upload_tmp_dir = /var/www/tmp
...
; Maximum size of POST data that PHP will accept.
; Its value may be 0 to disable the limit. It is ignored if POST data reading
; is disabled through enable_post_data_reading.
; http://php.net/post-max-size
post_max_size = 512M
...
; Maximum allowed size for uploaded files.
; http://php.net/upload-max-filesize
upload_max_filesize = 512M
...

```

5. Dienste aktivieren und neustarten

- **sudo systemctl enable nginx.service php7.3-fpm.service**
- **sudo systemctl restart nginx.service php7.3-fpm.service**

Nextcloud

1. Nextcloud-Verzeichnisse erstellen

- **sudo mkdir /var/www/{public_html,data,tmp}**

Es wurde eine bereits bestehende Installation übernommen.

Backup mit Borgmatic

1. Installation siehe [mariadb](#)
2. Konfiguration

/etc/borgmatic/config.yaml

```

...
location:
  # List of source directories to backup (required). Globs and
  # tildes are expanded.
  source_directories:
    - /etc
    - /home

```

- /root
- /var/log
- /var/www

...

Dauerhafter Link zu diesem Dokument:

<https://wiki.technikkultur-erfurt.de/dienste:bytecluster0002:cloud?rev=1613908616>

Dokument zuletzt bearbeitet am: **21.02.2021 11:56**

Verein zur Förderung von Technikkultur in Erfurt e.V

<https://wiki.technikkultur-erfurt.de/>

