

Container 'cloud'

Ressourcen

- 1 GB RAM
- 2 Cores
- 5 GB HDD (root-fs)
- 40 GB HDD (/var/www)

System

- interne IPs
 - 10.2.0.14, fd00:10:2:0::14
 - 10.3.0.14, fd00:10:3:0::14

Dienste

- Nextcloud (via NGINX)

Betrieb

Nextcloud aktualisieren (auf der Konsole)

1. Updater ausführen
 - **sudo -u www-data php /var/www/public_html/updater/updater.phar**
 - Start update? [y/N] **y**
 - Should the „occ upgrade“ command be executed? [Y/n] **y**
 - Keep maintenance mode active? [y/N] **n**
2. In Nextcloud einloggen und unter [Einstellungen - Verwaltung - Übersicht](#) prüfen. Folgende Fehler sind „normal“:
 - Dein Web-Server ist nicht richtig eingerichtet um „/.well-known/caldav“ aufzulösen.
 - Dein Web-Server ist nicht richtig eingerichtet um „/.well-known/carddav“ aufzulösen.
 - Es wurde kein PHP-Memory-Cache konfiguriert.
3. Angezeigte Fehler prüfen und korrigieren
 1. Nutzung von OCC: **sudo -u www-data /var/www/public_html/occ ...**

Backup

Dateien per Shell sichern

```
- cd /var/www/public_html
- sudo -u www-data php occ maintenance:mode --on
- sudo tar -cpzf //nc_backup_`date +%Y%m%d`.tar.gz -C /var/www/public_html/ .
```

Installation

- Standard-Template mit Benutzern

NGINX / PHP

1. NGINX und PHP-FPM installieren
 - **sudo apt-get install php8.2 php8.2-cli php8.2-fpm php8.2-curl php8.2-gd php8.2-xml php8.2-mbstring php8.2-zip php8.2-mysql php8.2-bz2 php8.2-intl php8.2-bcmath php8.2-gmp php-imagick nginx**
2. Default-Konfiguration anpassen

/etc/nginx/sites-available/default

```
server {
    listen 80 default_server;
    listen [::]:80 default_server;
```

```

root /var/www/public_html;

# Add index.php to the list if you are using PHP
index index.php index.html /index.php$request_uri;

server_name _;

# set max upload size
client_max_body_size 512M;
fastcgi_buffers 64 4K;

# Enable gzip but do not remove ETag headers
gzip on;
gzip_vary on;
gzip_comp_level 4;
gzip_min_length 256;
gzip_proxied expired no-cache no-store private no_last_modified no_etag auth;
gzip_types application/atom+xml application/javascript application/json
application/ld+json application/manifest+json application/rss+xml
application/vnd.geo+json application/vnd.ms-fontobject application/x-font-ttf
application/x-web-app-manifest+json application/xhtml+xml application/xml font/opentype
image/bmp image/svg+xml image/x-icon text/cache-manifest text/css text/plain text/vcard
text/vnd.rim.location.xloc text/vtt text/x-component text/x-cross-domain-policy;

# HTTP response headers borrowed from Nextcloud `.htaccess`
add_header Referrer-Policy "no-referrer" always;
add_header X-Content-Type-Options "nosniff" always;
add_header X-Download-Options "noopen" always;
add_header X-Frame-Options "SAMEORIGIN" always;
add_header X-Permitted-Cross-Domain-Policies "none" always;
add_header X-Robots-Tag "noindex,nofollow"
always;
add_header X-XSS-Protection "1; mode=block" always;

# Remove X-Powered-By, which is an information leak
fastcgi_hide_header X-Powered-By;

# Rule borrowed from `.htaccess` to handle Microsoft DAV clients
location = / {
    if ( $http_user_agent ~ ^DavClnt ) {
        return 302 /remote.php/webdav/$is_args$args;
    }
}

location = /robots.txt {
    allow all;
    log_not_found off;
    access_log off;
}

# Make a regex exception for `/.well-known` so that clients can still
# access it despite the existence of the regex rule
# `location ~ /\.(|autotest|...)` which would otherwise handle requests
# for `/.well-known`.
location ^~ /.well-known {
    # The following 6 rules are borrowed from `.htaccess`
    last;
    rewrite ^/\.(well-known)/host-meta\.json /public.php?service=host-meta
last;
    rewrite ^/\.(well-known)/host-meta /public.php?service=host-meta
last;
    rewrite ^/\.(well-known)/webfinger /public.php?service=webfinger

```

```

last;
    rewrite ^/\..well-known/nodeinfo /public.php?service=nodeinfo
last;
    location = /.well-known/carddav { return 301 /remote.php/dav/; }
    location = /.well-known/caldav { return 301 /remote.php/dav/; }
    try_files $uri $uri/ =404;
}

# Rules borrowed from `.htaccess` to hide certain paths from clients
location ~ ^/(?:(build|tests|config|lib|3rdparty|templates|data)(?:$|/)) {
return 404; }
location ~ ^/(?!(\..|autotest|occ|issue|indie|db_|console)) { return
404; }

# Ensure this block, which passes PHP files to the PHP process, is above the
blocks
# which handle static assets (as seen below). If this block is not declared
first,
# then Nginx will encounter an infinite rewriting loop when it prepends
`/index.php`
# to the URI, resulting in a HTTP 500 error response.
location ~ \.php(?:$|/) {
    fastcgi_split_path_info ^(.+?\.php)(/.*)$;
    set $path_info $fastcgi_path_info;

    try_files $fastcgi_script_name =404;

    include fastcgi_params;
    fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;
    fastcgi_param PATH_INFO $path_info;
    fastcgi_param HTTPS on;

    fastcgi_param modHeadersAvailable true;      # Avoid sending the
security headers twice
    fastcgi_param front_controller_active true;  # Enable pretty urls
    #fastcgi_pass php-handler;
    fastcgi_pass unix:/run/php/php8.2-fpm.sock;

    fastcgi_intercept_errors on;
    fastcgi_request_buffering off;
}

location ~ \.(?:css|js|svg|gif)$ {
    try_files $uri /index.php$request_uri;
    expires 6M;          # Cache-Control policy borrowed from `.htaccess`
    access_log off;     # Optional: Don't log access to assets
}

location ~ \.woff2?$ {
    try_files $uri /index.php$request_uri;
    expires 7d;          # Cache-Control policy borrowed from `.htaccess`
    access_log off;     # Optional: Don't log access to assets
}

location / {
    try_files $uri $uri/ /index.php$request_uri;
}
}

```

3. PHP-Konfiguration für Upload anpassen

```
/etc/php/8.2/fpm/pool.d/www.conf
```

```
...
clear_env = no
...
env[HOSTNAME] = $HOSTNAME
env[PATH] = /usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin
env[TMP] = /tmp
env[TMPDIR] = /tmp
env[TEMP] = /tmp
...
```

4. PHP-Konfiguration für Upload anpassen

```
/etc/php/8.2/fpm/conf.d/99-local.ini
```

```
output_buffering = 0
max_execution_time = 1800
max_input_time = 1800
memory_limit = 512M
upload_tmp_dir = /var/www/tmp
post_max_size = 512M
upload_max_filesize = 512M
```

5. Dienste aktivieren und neustarten

- **sudo systemctl enable nginx.service php8.2-fpm.service**
- **sudo systemctl restart nginx.service php8.2-fpm.service**

Nextcloud

1. Nextcloud-Verzeichnisse erstellen
 - **sudo mkdir /var/www/{public_html,data,tmp}**
2. Cronjob einrichten
 - **sudo crontab -u www-data -e**

```
*/5 * * * * php -f /var/www/public_html/cron.php
```

Es wurde eine bereits bestehende Installation übernommen.

Backup mit Borgmatic

1. Installation siehe [mariadb](#)
2. Konfiguration

```
/etc/borgmatic/config.yaml
```

```
...
location:
  # List of source directories to backup (required). Globs and
  # tildes are expanded.
  source_directories:
    - /etc
    - /home
    - /root
    - /var/log
    - /var/www/data
    - /var/www/public_html
...
```

Dauerhafter Link zu diesem Dokument:

<https://wiki.technikkultur-erfurt.de/dienste:bytecluster0002:cloud?rev=1741389391>

Dokument zuletzt bearbeitet am: **07.03.2025 23:16**



Verein zur Förderung von Technikkultur in Erfurt e.V

<https://wiki.technikkultur-erfurt.de/>