

Container 'mariadb'

Ressourcen

- 1 GB RAM
- 2 Cores
- 8 GB HDD (root-fs)

System

- interne IPs
 - 10.2.0.100, fd00:10:2:0::100
 - 10.3.0.100, fd00:10:3:0::100 (MariaDB)

Dienste

- MariaDB 10

Datenbanken

Datenbank	Benutzer	Verwendung
nextcloud	nc_user	Nextcloud
wordpress	wp_user	Wordpress
wordpress_technikkultur	wp_tk	Wordpress Technikkultur
paste	paste	paste

Betrieb

Datenbank und Benutzer anlegen

1. Zur Datenbank verbinden
 - **sudo mysql**
2. Datenbank anlegen und Benutzer mit Passwort zuweisen

MySQL-Konsole "MariaDB [(none)]"

```
CREATE DATABASE databasename;  
GRANT ALL PRIVILEGES ON databasename.* TO 'username'@'%' IDENTIFIED BY 'password';  
FLUSH PRIVILEGES;
```

Passwort für Benutzer ändern

1. Zur Datenbank verbinden
 - **sudo mysql**
2. Benutzer neues Passwort zuweisen

MySQL-Konsole "MariaDB [(none)]"

```
ALTER USER 'username'@'%' IDENTIFIED BY 'password';  
FLUSH PRIVILEGES;
```

Installation

- Standard-Template mit Benutzern

MariaDB

1. MariaDB-Server installieren

- **apt-get install mariadb-server**
- 2. MariaDB - Erstkonfiguration
 - **mysql_secure_installation**
 - Set root password? [Y/n]: **Y**
 - New password: **PASSWORT**
 - Re-enter new password: **PASSWORT**
 - Remove anonymous users? [Y/n]: **Y**
 - Disallow root login remotely? [Y/n]: **Y**
 - Remove test database and access to it? [Y/n]: **Y**
 - Reload privilege tables now? [Y/n]: **Y**
- 3. Benutzerdefinierte Konfiguration anlegen

/etc/mysql/mariadb.conf.d/99-bytecluster.cnf

```
[mysqld]
# An lokale IP binden
bind-address                = 10.3.0.100

# Binlog deaktivieren
skip-log-bin

# InnoDB verwenden
default_storage_engine     = InnoDB

# InnoDB-Optimierungen
innodb_buffer_pool_size   = 256M
innodb_log_buffer_size    = 8M
innodb_log_file_size      = 128M

innodb_log_files_in_group = 2
innodb_flush_log_at_trx_commit = 2
innodb_flush_method       = 0_DIRECT
innodb_file_per_table     = 1
```

- 4. MariaDB neustarten
 - **systemctl restart mariadb.service**

Backup mit Borgmatic

- 1. Debian Testing-Repo „Bullseye) integrieren (für Borgmatic 1.5, da Debian 10 noch Borgmatic 1.2 beinhaltet)
 - Standard-Installationsquelle auf „stable“ stellen und borgmatic aus testing installieren

/etc/apt/preferences.d/testing

```
Explanation: Uninstall or do not install any Debian-originated
Explanation: package versions other than those in the stable distro
Package: *
Pin: release a=stable
Pin-Priority: 900

Package: borgmatic
Pin: release o=Debian,a=testing
Pin-Priority: 500

Package: *
Pin: release o=Debian
Pin-Priority: -10
```

- Testing-Repo integrieren

/etc/apt/sources.list.d/hetzner-mirror-testing.list


```

- repository
- archives
...
hooks:
  before_backup:
    - dpkg-query -f '${binary:Package}\n' -W > /root/package.list
    ...
  mysql_databases:
    - name: all
    ...

```

9. Borg-Repository initialisieren
 - o **sudo borgmatic init --encryption keyfile**
10. Verschlüsselungsinformationen sicher verwahren
 1. Verschlüsselungs-Passwort ermitteln
 - **sudo grep "encryption_passphrase:" /etc/borgmatic/config.yaml**
 2. Verschlüsselungs-Schlüssel ermitteln
 - **sudo cat /root/.config/borg/keys/SERVERNAME-MIT-UNTERSTRICHEN__borg**
11. Erstes Backup initialisieren
 - o **sudo borgmatic create --progress --stats**

```

-----
Archive name: mariadb-2020-12-05T17:36:48.502653
Archive fingerprint:
9a9c7f769dcd9af1e7f28158e4a3b0d05cb3faae25c45a6e9930591a1414eaa3
Time (start): Sat, 2020-12-05 17:36:49
Time (end):   Sat, 2020-12-05 17:36:55
Duration: 6.57 seconds
Number of files: 472
Utilization of max. archive size: 0%
-----

```

	Original size	Compressed size	Deduplicated size
This archive:	71.08 MB	2.72 MB	2.53 MB
All archives:	71.08 MB	2.72 MB	2.53 MB

```

-----

```

	Unique chunks	Total chunks
Chunk index:	437	464

```

-----

```

12. Backupinhalt nochmal prüfen
 - o **sudo borgmatic list --archive latest**

```

USERNAME@SERVERNAME:~/borg: Listing archives
drwxr-xr-x root root      0 Wed, 2020-11-25 19:49:45 etc
-rw-r--r-- root root    767 Fri, 2016-03-04 11:00:00 etc/profile
...

```

13. Cronjob einrichten
 - o **echo -e "0 3 * * *\troot\t\$(which borgmatic) --syslog-verbosity 1" | sudo tee /etc/cron.d/borgmatic > /dev/null**

Dauerhafter Link zu diesem Dokument:
<https://wiki.technikkultur-erfurt.de/dienste:bytecluster0002:mariadb?rev=1609284120>

Dokument zuletzt bearbeitet am: **29.12.2020 23:22**

Verein zur Förderung von Technikkultur in Erfurt e.V
<https://wiki.technikkultur-erfurt.de/>

