Proxmox container 'nextcloud.test'

Container setup

- IP: 10.2.0.20
- image: debian10 with users

Ansible setup

- verbindet man sich als unpriviligierter user und möchte ein Command als ein anderer, unpriviligierter user ausführen (z.B. www-data), benötigt man

  ```
  allow_world_readable_tmpfiles = yes
  ```

  in der ansible.cfg, damit dies nicht als Fehler zum Abbruch führt.

Ansible Script

```
#!/usr/bin/env ansible-playbook

- name: 'install nextcloud'
  hosts: nextcloud
  become: true

  tasks:
  - name: install packages
    apt:
      pkg:
        - php7.3
        - php7.3-curl
        - php7.3-gd
        - php7.3-json
        - php7.3-xml
        - php7.3-mbstring
        - php7.3-zip
        - php7.3-mysql
        - php7.3-bz2
        - php7.3-intl
        - php7.3-redis
        - php7.3-imagick
        - ffmpeg

  - name: Download nextcloud and unpack
    unarchive:
      src: https://download.nextcloud.com/server/releases/nextcloud-20.0.0.zip
      dest: /var/www
      owner: www-data
      group: www-data
      remote_src: yes

  - name: Remove file packed file
    file:
      path: /var/www/nextcloud-20.0.0.zip
      state: absent
```

```
- name: first setup nextcloud
  become_user: www-data
  become: yes
  shell: >
    php occ  maintenance:install
    --database mysql
    --database-host 10.3.0.100
    --database-name nextcloud
    --database-table-prefix nc
    --database-user nc_user
    --database-pass <pass>
    --admin-user admin
    --admin-pass <pass>
    --data-dir /var/www/nextcloud/data
  args:
    chdir: /var/www/nextcloud/
    creates: /var/www/nextcloud/config/config.php

- name: copy nginx config
  copy:
    src: ./conf/nextcloud.conf
    dest: /etc/nginx/sites-available/
    owner: root
    group: root
    mode: '0744'

- name: Create a symbolic link
  file:
    src: /etc/nginx/sites-available/nextcloud.conf
    dest: /etc/nginx/sites-enabled/nextcloud.conf
    owner: root
    group: root
    state: link

- name: load php-fpm
  systemd:
    state: restarted
    name: php7.3-fpm

- name: Restart nginx
  systemd:
    state: restarted
    daemon_reload: yes
    name: nginx
```

Dauerhafter Link zu diesem Dokument:
https://wiki.technikkultur-erfurt.de/dienste:bytecluster0002:nextcloud?rev=1601836989

Dokument zuletzt bearbeitet am: **04.10.2020 18:43**

Verein zur Förderung von Technikkultur in Erfurt e.V
https://wiki.technikkultur-erfurt.de/